



Specifications Philips CoreLine LED  
Downlight DN131B 3000K 1000lm  
LED10S PSED-E II ALU | DALI  
Dimmable

[View Product](#)

General Information

|                          |                                 |
|--------------------------|---------------------------------|
| SKU                      | 214403                          |
| EAN                      | 8718696852279                   |
| Brand                    | Philips                         |
| Manufacturer Name        | DN131B LED10S/830 PSED-E II ALU |
| Any Lamp all-in warranty | 5 Years                         |
| Average Lifetime (h)     | 50000                           |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Including bulb              | Yes               |
| Driver Included             | Yes               |

|                          |                                    |
|--------------------------|------------------------------------|
| Beam Angle (degree)      | 120                                |
| Luminous Efficacy (lm/W) | 90.9                               |
| Power factor             | >0.90                              |
| Installation Depth (mm)  | 130                                |
| Unified Glare Rating     | < 25 - for hallways and staircases |
| Suitable for Outdoor     | No                                 |
| Finish of Reflector      | Frosted                            |
| Product Type Category    | LED Downlight                      |

## Fixture Information

|                        |                                         |
|------------------------|-----------------------------------------|
| EOC8                   | 85227900                                |
| Mounting Method        | Recessed                                |
| Cut out (mm)           | 150                                     |
| IP-rating              | IP20                                    |
| Impact Protection (IK) | IK02 - 0.20 joule                       |
| Operating Temperature  | -10 to +40                              |
| Housing                | PC (Polycarbonate)                      |
| Colour of the Fixture  | White                                   |
| Colour of material     | White                                   |
| Fixture Connection     | PIP [Push-in connector and pull relief] |
| Series                 | DN131B                                  |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 103 |
| Diameter (mm) | 166 |

## Sensor Information

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

