



Specifications Philips LED Panel FlexBlend SM340C  
26W 3500lm - 930 Warm White | 150x20cm - UGR <19  
- Zigbee Dimmable - Best Colour Rendering

[View Product](#)

## General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 238813                              |
| EAN                      | 8719514103863                       |
| Brand                    | Philips                             |
| Manufacturer Name        | SM340C 35S/930 SRD PCS SWZU L150 WH |
| Any Lamp all-in warranty | 5 Years                             |
| Average Lifetime (h)     | 50000                               |
| Series                   | Panel Led                           |

## Technical Information

|                             |                      |
|-----------------------------|----------------------|
| Technology                  | LED Integrated       |
| Wireless connection         | Zigbee               |
| Lighting Control            | Zigbee               |
| Voltage (V)                 | 220-240              |
| Dimmable                    | Dimmable with Zigbee |
| Colour Code                 | 930 Warm White       |
| Colour temperature (Kelvin) | 3000 Warm White      |
| Colour Rendering (Ra)       | 90-99                |
| Colour of Light             | White                |
| Light colour options        | Single Color         |
| Luminous Efficacy (lm/W)    | 135                  |

|                        |                   |
|------------------------|-------------------|
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Terminal, 5-pole  |
| Driver Included        | Yes               |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x20cm |
| Length (mm)    | 1470     |
| Width (mm)     | 200      |
| Height (mm)    | 73       |

## Why Any-lamp?

## Sensor Information


**Order from the largest lighting specialist in Europe**


**Customised quotation**


**Up to 7 years warranty**


**Easy return process**